

EA200

400VA~2000VA




Features

- LED display or LCD display for option
- Microprocessor-based digital control
- Boost and buck AVR for voltage stabilization
- Frequency adaptive
- Humanized alarm system
- Automatically diagnose when starts
- Cold start
- Auto restart while AC is recovering
- Simulated sine wave output
- Intelligent battery management
- Short circuit and over discharged protection
- Automatically charging battery at UPS off mode
- Shut down when no load connected at battery mode (optional for LCD mode)
- Optional RS232/USB communication port and RJ11/RJ45 protection

Rear Panel

1. Output Socket (Selectable)
2. TEL/Modem/Fax surge protection (Optional)
3. USB (Optional)
4. AC Input
5. Fuse



Optional socket



450-850VA



1200VA



1500-2000VA

Specifications

MODEL		EA245	EA265	EA275	EA285	EA2120	EA2150	EA2200
Capacity		450VA 240W	650VA 360W	750VA 420W	850VA 480W	1200VA 720W	1500VA 900W	2000VA 1200W
INPUT								
Voltage		100V/110V/120VAC ± 25% or 220V/230V/240VAC ± 25% (–35%optional)						
Frequency		50/60Hz ± 10%(Auto Sensing)						
OUTPUT								
Voltage		100V/110V/120VAC ± 10% or 220V/230V/240VAC ± 10%						
Frequency		50/60Hz ± 1% (Auto Sensing)						
Waveform		AC mode: Pure sine wave, Battery mode :Simulated sine wave						
Crest Factor		3:1						
Transfer Time		Typical 2–7ms, 10ms max						
BATTERY								
DC Voltage		12V				24V		
Configuration		1x12V/4.5AH	1x12V/7.0AH	1x12V/7.0AH	1x12V/8.0AH	2x12V/7.0AH	2x12V/8.0AH	2x12V/9.0AH
Typical Recharge Time		6–8 hours recover to 90% capacity						
PROTECTION								
Full Protection		Short circuit, Battery over–charge and over discharge protection						
ENVIRONMENT								
Humidity		20–90% RH @ 0–40°C(non–condensing)						
Noise Level		≤45dB (1m)						
MANAGEMENT								
USB/RS–232/SNMP(Option)		Supports Windows® 98/2000/2003/XP/Vista/2008/ Windows® 7/8						
PHYSICAL								
Plastic case	Net/Gross Weight(kg)	3.8/4.3	4.3/4.8	4.8/5.3	5.3/5.8	9.5/10.0	10.7/11.2	11.2/11.7
	Dimension(mm) WxDxH	100x280x140				140x345x170	—	
	Packing Dimension (mm) WxDxH	147x338x210				198x406x245	—	
	Quantity/20ft	2300PCS				1000PCS		
Metal case	Net/Gross Weight(kg)	4.5/5.0	5.5/6.0	6.0/6.5	6.7/7.2	10.5/11.2	12.6/13.4	14.0/14.8
	Dimension(mm) WxDxH	95x280x165	95x320x165			125x320x220	125x380x220	
	Packing Dimension (mm) WxDxH	145x315x230	145x375x230			180x390x295	180x450x295	
	Quantity/20ft	2400PCS	2000PCS			1000PCS		
Rack mount	Net/Gross Weight(kg)	6.7/7.2	7.8/8.3	8.0/8.5	9.0/9.5	12.6/13.2	15.7/16.3	17.0/17.6
	Dimension(mm) WxDxH	440x310x88				440x310x132		
	Packing Dimension (mm) WxDxH	535x400x180				535x400x230		

- All specifications subject to change without notice.
- Custom-made specifications are acceptable